


TG2000 Software

PC Based Software Package used for City Multi and Mr Slim

The TG2000 centralised PC based graphical software package allows the operator to control and monitor up to a maximum of 2000 indoor units. This software has been designed to connect directly to a City Multi or Mr Slim system via G50 controllers, allowing the operator all the required functionality to control and monitor the complete air conditioning system from a central location. In addition to providing a centralised control facility, the TG2000 allows complete energy consumption data to be logged with user definable billing groups and electrical tariffs for billing purposes.



<<Technical Information

TG2000 PC Based software that works in conjunction with G50 Centralised Controllers	
FUNCTION	DESCRIPTION
OPERATING PLATFORM	Pentium III , CPU 350Mhz or faster for less than 1000 indoor units. 1000Mhz for up to 2000 indoor units. 128MB ram, Windows 2000 pro. 6GB or more. Internal LAN 10/100 Mbps
MAX No. OF INDOOR UNITS	2000 Indoor units, 50 indoor units per G50 centralised controller
OPERATIONAL SECTIONS	The software package is split into two distinctive areas, System and Controls setting. System Setting: Password protected , System Configuration and group/block organisation, printer setting. Controls Setting: Normal Operation, monitoring and control functions as described below. The software allows individual indoor units to be allocated to logical groups, represented within user definable graphics screens, allocated during the system configuration
ON/OFF	Indicates the On/Off status of each group within the selected graphical screen or entire building
OPERATION MODE	Indicates the operational mode (Cool, Heat, Fan, Dry, Auto) for each group on the selected graphical screen
SET TEMPERATURE	Displays the set temperature for each group on the selected graphical screen. Also able to limit the set point range in both heating and cooling mode
AIR SPEED	Displays the current fan speed setting for each group on the selected graphical screen
REMOTE CONTROLLER PROHIBIT/PERMIT	Displays the current prohibit/permit status for each groups remote controller on the selected graphical screen
ABNORMALITY (FAULT) MONITORING	Individual indoor unit fault monitoring is recorded within the fault log for both viewing and printing. Fault monitoring can also be viewed via the fault log for all units associated with a particular graphical screen or the entire building. Faults can also be tracked and printed using date of failure, date of recovery and error code
ROOM TEMPERATURE MONITORING	Displays the return air temperature of the master indoor unit within a group
SCHEDULED ON/OFF	On/Off schedules can be set for each group, each graphical screen or the entire building
ENERGY CHARGING	Able to create bills for individual indoor units, groups of indoor units or a complete system
ENERGY SAVE CONTROL	Individual indoor unit, group of indoor units or a complete system can be controlled. There are various energy saving options available
TREND LOGGING	Able to log: Return air temperature, setpoint, mode, On/Off, power consumption by group or by indoor unit, watt-hour meter
GRAPHICAL SCREENS	The complete system configurations can be allocated between multiple screens. Each screen can display a bitmap image representing the area of the building or floor where the units or groups are physically located



This pdf has been downloaded from the website of :

“Supplying and installing the latest in air conditioning technology”

° Celsius
air conditioning

Celsius Air Conditioning Ltd, 1 Well Street, Heywood, Greater Manchester OL10 1NT

 01706 367 500  07000 CELSIUS  01706 367 355  sales@celsiusair.co.uk  www.celsiusair.co.uk

www.celsiusair.co.uk