

PLFY-P-VLMD-E

2-Way Blow Ceiling Cassette Indoor Unit

The PLFY-P-VLMD-E cassette unit fits into the space in a suspended ceiling to provide heating or cooling. This new unit has been redesigned with lower unit height and lower noise levels.

- > Light unit for ease of installation
- > Terminal block on outside of unit for easy wiring
- > Drain lift-pump mechanism as standard
- > Newly designed decoration panel with air flow switching and swing functions as standard



Technical Information >>

PLFY-P-VLMD-E - INDOOR UNIT

MODEL REFERENCE		PLFY-P20VLMD-E	PLFY-P25VLMD-E	PLFY-P32VLMD-E	PLFY-P40VLMD-E	PLFY-P50VLMD-E	PLFY-P63VLMD-E	PLFY-P80VLMD-E	PLFY-P100VLMD-E	PLFY-P125VLMD-E
CAPACITY (kW)	Heating (nominal)	2.5	3.2	4.0	5.0	6.3	8.0	10.0	12.5	16.0
	Cooling (nominal)	2.2	2.8	3.6	4.5	5.6	7.1	9.0	11.2	14.0
R410A / R407c	Heating (UK)	2.3	3.0	3.7	4.6	5.8	7.4	9.2	11.6	14.8
R410A	Cooling (UK)	2.1	2.6	3.4	4.3	5.3	6.7	8.5	10.6	13.2
R407c	Cooling (UK)	2.1	2.7	3.4	4.3	5.3	6.7	8.6	10.6	13.3
R410A High Sensible	Cooling (UK)	1.6	2.0	2.6	3.3	4.1	5.2	6.5	8.1	10.2
SHF	R410A (UK)	0.81	0.77	0.74	0.67	0.70	0.72	0.71	0.73	0.73
	R407c (UK)	0.76	0.70	0.71	0.72	0.70	0.75	0.70	0.76	0.74
High Sensible	R410A (UK)	0.94	0.85	0.81	0.73	0.73	0.77	0.77	0.79	0.80
POWER INPUT (kW)	Heating (nominal)	0.065	0.065	0.065	0.074	0.075	0.094	0.140	0.150	0.27
	Cooling (nominal)	0.072	0.072	0.072	0.081	0.082	0.101	0.147	0.157	0.28
AIRFLOW (m3/min)	Lo-Mi1-Mi2-Hi	6.5-8.0-9.5	6.5-8.0-9.5	6.5-8.0-9.5	7.0-8.5-10.5	9.0-11.0-12.5	10.0-13.0-15.5	15.5-18.5-22.0	17.5-21.0-25.0	24-27-30-33
NOISE (dBA)	Lo-Mi1-Mi2-Hi	27-30-33	27-30-33	27-30-33	29-33-36	31-34-37	32-37-39	33-36-39	36-39-42	40-42-44-46
WEIGHT (kg)	(Grille)	23(6.5)	23(6.5)	24(6.5)	24(6.5)	27(7.5)	28(7.5)	44(12.5)	47(12.5)	56(13)
DIMENSIONS (mm)	Width (Grille)	776(1080)	776(1080)	776(1080)	776(1080)	946(1250)	946(1250)	1446(1750)	1446(1750)	1708(2010)
	Depth (Grille)	634(710)	634(710)	634(710)	634(710)	634(710)	634(710)	634(710)	634(710)	606(710)
	Height (Grille)	290(20)	290(20)	290(20)	290(20)	290(20)	290(20)	290(20)	290(20)	290(20)
ELECTRICAL SUPPLY		220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz
PHASE		Single	Single	Single	Single	Single	Single	Single	Single	Single
RUNNING CURRENT (A)	Heating	0.30	0.30	0.30	0.34	0.35	0.43	0.66	0.69	1.33
	Cooling	0.36	0.36	0.36	0.40	0.41	0.49	0.72	0.75	1.35
FUSE RATING (BS88) – HRC (A)		6	6	6	6	6	6	6	6	6
MAINS CABLE No. Cores		3	3	3	3	3	3	3	3	3
GRILLE MODEL REFERENCE		CMP-40VLV-B	CMP-40VLV-B	CMP-40VLV-B	CMP-40VLV-B	CMP-63VLV-B	CMP-63VLV-B	CMP-100VLV-B	CMP-100VLV-B	CMP-125VLV-B

PLFY-P-VLMD-E

This pdf has been downloaded from the website of :

“Supplying and installing the latest in air conditioning technology”



Celsius Air Conditioning Ltd, 1 Well Street, Heywood, Greater Manchester OL10 1NT

 01706 367 500  07000 CELSIUS  01706 367 355  sales@celsiusair.co.uk  www.celsiusair.co.uk

www.celsiusair.co.uk