

PLA-RP Power Inverter Heat Pump

R410A 4-Way Blow Ceiling Cassette System

New Models

- > Airflow controllable for ceiling heights up to 4.2m
- > Electronic fan speed control
- > Quiet start up cycle



Technical Information >>

PLA-RP - INDOOR UNITS								
MODEL REFERENCE		PLA-RP35AA	PLA-RP50AA	PLA-RP60AA	PLA-RP71AA	PLA-RP100AA	PLA-RP125AA	PLA-RP140AA
CAPACITY (kW)	Heating (nominal)	4.1 (1.6-5.2)	6.0 (2.5-7.3)	7.0 (2.8-8.2)	8.0 (3.5-10.2)	11.2 (4.5-14.0)	14.0 (5.0-16.0)	16.0 (5.0-18.0)
	Cooling (nominal)	3.6 (1.6-4.5)	5.0 (2.3-5.6)	6.0 (2.7-6.7)	7.1 (3.3-8.1)	10.0 (4.9-11.4)	12.5 (5.5-14.0)	14.0 (5.5-15.3)
	Heating (UK)	3.5 (1.35-4.4)	5.1 (2.15-6.2)	5.95 (2.4-6.95)	6.8 (3.0-8.65)	9.5 (3.85-11.9)	11.9 (4.25-13.6)	13.6 (4.25-15.3)
	Cooling (UK)	3.25 (1.45-4.05)	4.5 (2.05-5.05)	5.4 (2.45-6.05)	6.4 (2.95-7.3)	9.0 (4.4-10.25)	11.25 (4.95-13.75)	12.6 (4.95-13.75)
SHF (nominal)		0.89	0.86	0.78	0.74	0.75	0.74	0.71
COP / EER (nominal)		3.66 / 3.36	3.70 / 3.23	3.78 / 3.64	3.42 / 3.60	3.30 / 3.30	3.28 / 3.21	3.26 / 2.81
ENERGY LABEL Heating/Cooling		A / A	A / A	A / A	B / A	C / A	C / A	C / C
AIRFLOW (m3/min)		Lo-Mi1-Mi2-Hi	11-12-13-14	14-15-16-18	15-16-18-20	20-23-26-28	22-25-28-30	22-25-28-30
PIPE SIZE mm(in)	Gas	12.7 (1/2")	12.7 (1/2")	15.88 (5/8")	15.88 (5/8")	15.88 (5/8")	15.88 (5/8")	15.88 (5/8")
	Liquid	6.35 (1/4")	6.35 (1/4")	9.52 (3/8")	9.52 (3/8")	9.52 (3/8")	9.52 (3/8")	9.52 (3/8")
NOISE (dBA)		Lo-Mi1-Mi2-Hi	27-28-29-31	28-29-31-33	28-30-32-34	33-36-39-41	37-40-43-45	37-40-43-45
DIMENSIONS (mm) (Grille)	Width	840 (950)	840 (950)	840 (950)	840 (950)	840 (950)	840 (950)	840 (950)
	Depth	840 (950)	840 (950)	840 (950)	840 (950)	840 (950)	840 (950)	840 (950)
	Height	258 (30)	258 (30)	258 (30)	258 (30)	298 (30)	298 (30)	298 (30)
WEIGHT (kg)	Unit	24	24	24	24	30	32	32
	Panel	5	5	5	5	5	5	5
ELECTRICAL SUPPLY		Fed by Outdoor Unit	Fed by Outdoor Unit	Fed by Outdoor Unit	Fed by Outdoor Unit	Fed by Outdoor Unit	Fed by Outdoor Unit	Fed by Outdoor Unit
PHASE		Single	Single	Single	Single	Single	Single	Single
FUSE RATING (BS88) – HRC (A)		6	6	6	6	6	6	6
INTERCONNECTING CABLE No. CORES		4	4	4	4	4	4	4
GRILLE REFERENCE		PLP-6AA	PLP-6AA	PLP-6AA	PLP-6AA	PLP-6AA	PLP-6AA	PLP-6AA
WIRED REMOTE CONTROLLER REFERENCE		PAR-21MAA	PAR-21MAA	PAR-21MAA	PAR-21MAA	PAR-21MAA	PAR-21MAA	PAR-21MAA

PUHZ-RP - OUTDOOR UNITS								
MODEL REFERENCE		PUHZ-RP35VHA	PUHZ-RP50VHA	PUHZ-RP60VHA	PUHZ-RP71VHA	PUHZ-RP100VHA/YHA	PUHZ-RP125VHA/YHA	PUHZ-RP140VHA/YHA
NOISE (dBA) Heating/Cooling		46 / 44	46 / 44	48 / 47	48 / 47	51 / 49	52 / 50	52 / 50
WEIGHT (kg)		45	45	75	75	121 / 135	121 / 135	121 / 135
DIMENSIONS (mm)	Width	800	800	950	950	950	950	950
	Depth	330 + 23	330 + 23	330 + 30	330 + 30	330 + 30	330 + 30	330 + 30
	Height	600	600	943	943	1350	1350	1350
ELECTRICAL SUPPLY		220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz / 380-415,50Hz	220-240v, 50Hz / 380-415,50Hz	220-240v, 50Hz / 380-415,50Hz
PHASE		Single	Single	Single	Single	Single / 3	Single / 3	Single / 3
SYSTEM POWER INPUT (kW)	Heating/Cooling (nominal)	1.12 / 1.07	1.62 / 1.55	1.85 / 1.65	2.34 / 1.97	3.39 / 3.03	4.27 / 3.89	4.91 / 4.99
	Heating/Cooling (UK)	1.00 / 0.91	1.44 / 1.32	1.65 / 1.40	2.08 / 1.68	3.02 / 2.58	3.80 / 3.31	4.37 / 4.25
STARTING CURRENT (A)		5	5	5	5	5	5	5
SYSTEM RUNNING CURRENT (A) Single Phase	Heating/Cooling	5.02 / 4.8	7.26 / 6.95	8.29 / 7.4	10.53 / 8.83	15.19 / 13.58	19.14 / 17.44	22.01 / 22.37
	3 Phase	-	-	-	-	5.58 / 5.04	7.05 / 6.49	8.01 / 8.13
FUSE RATING (BS88) – HRC (A)		16	16	25	25	32 / 16	32 / 16	40 / 16
MAINS CABLE No. Cores		3	3	3	3	3 / 5	3 / 5	3 / 5
MAX PIPE LENGTH (m)		50	50	50	50	75	75	75
MAX HEIGHT DIFFERENCE (m)		30	30	30	30	30	30	30
CHARGE R410A (kg) - 30m		2.5	2.5	3.5	3.5	5.0	5.0	5.0

PLA-RP Power Inverter Heat Pump

Page 35

Technical drawing of the front view of a rectangular duct with a central circular branch duct hole. The main duct has a width of 840 and a height of 100. The branch duct hole has a diameter of 175. The distance from the center of the branch duct hole to the nearest side of the main duct is 350. The distance from the center of the branch duct hole to the nearest end of the main duct is 150. The drawing includes dimension lines and labels for "Branch duct hole (Cut out hole)", "840", "100", "175", "350", "150", "A", and "B".

Models	A	B
Size 35-71	241	258
Size 100-140	281	298

Technical drawing of the front view of the 1000W air purifier. The unit is rectangular with a central air filter area. Dimensions are provided in millimeters: overall width 950mm, overall height 577mm, air outlet hole width 411mm, air intake hole width 577mm, and air intake hole height 411mm. The top and bottom air outlet holes are 77mm wide and 51mm high. The side air intake holes are 77mm wide and 51mm high.

This pdf has been downloaded from the website of :

“Supplying and installing the latest in air conditioning technology”



Celsius Air Conditioning Ltd, 1 Well Street, Heywood, Greater Manchester OL10 1NT

 01706 367 500  07000 CELSIUS  01706 367 355  sales@celsiusair.co.uk  www.celsiusair.co.uk

www.celsiusair.co.uk