



PKFY-P32VHM-E

Indoor Unit

Wall Mounted

An elegant design combined with compact dimensions and quiet operation make the PKFY-P an ideal unit choice. Noise levels are significantly reduced thanks to a unique airflow passage design that not only makes the unit one of the quietest in the industry, but also suppresses condensation and prevents mixing with secondary air.

- Compact design
- Front grille opening for easy cleaning
- Front power supply for easy wiring after installation
- 5-way piping provides more flexibility in selection of installation sites




Pictures not to scale



PKFY-P32VHM-E	
Capacity (kW):	
Heating (Nominal)	4.0
Cooling (Nominal)	3.6
Heating (UK)	3.7
Cooling (UK)	3.4
R410A High Sensible Cooling (UK)	2.6
SHF R410A (UK)	0.76
SHF High Sensible R410A (UK)	0.85
Power Input (kW) Heating (Nominal)	0.03
Power Input (kW) Cooling (Nominal)	0.04
Airflow(m3/min) - Lo-Mi-Hi	9-10-11
Noise (dBA) - Lo-Mi-Hi	34-37-41
Width - mm	898
Depth - mm	249
Height - mm	295
Weight - kg	13
Electrical Supply	220-240v, 50Hz
Phase	Single
Mains Cable No. Cores	3
Running Current (A) - Heating	0.3
Running Current (A) - Cooling	0.4
Fuse Rating (BS88) - HRC (A)	6

PKFY-P32VHM-E





249



CELSIUS AIR CONDITIONING LTD 1, WELL STREET HEYWOOD **OL10 1NT** Tel: 01706 367500 Fax: 01706 367355

Telephone: 01707 282880

Email: air.conditioning@meuk.mee.com Website: http://www.mitsubishielectric.co.uk/aircon

Mitsubishi Electric reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement.

