



## PKFY-P63VKM-E

Indoor Unit

Wall Mounted



An elegant design combined with compact dimensions and quiet operation make the PKFY-P an ideal unit choice. Noise levels are significantly reduced thanks to a unique airflow passage design that not only makes the unit one of the quietest in the industry, but also suppresses condensation and prevents mixing with secondary air.

- Compact flat panel design
- Front grille opening for easy cleaning
- Front power supply for easy wiring after installation
- 5-way piping provides more flexibility in selection of installation sites




Pictures not to scale

## **Product Details**

PKFY-P63VKM-E	
Capacity (kW):	
Heating (Nominal)	8.0
Cooling (Nominal)	7.1
Heating (UK)	7.4
Cooling (UK)	6.7
R410A High Sensible Cooling (UK)	5.2
SHF R410A (UK)	0.78
SHF High Sensible R410A (UK)	0.85
Power Input (kW) Heating (Nominal)	0.04
Power Input (kW) Cooling (Nominal)	0.05
Airflow(m3/min) - Lo-Hi	16-20
Noise (dBA) - Lo-Hi	39-45
Width - mm	1170
Depth - mm	295
Height - mm	365
Weight - kg	21
Electrical Supply	220-240v, 50Hz
Phase	Single
Mains Cable No. Cores	3
Running Current (A) - Heating	0.3
Running Current (A) - Cooling	0.37
Fuse Rating (BS88) - HRC (A)	6

## Dimensions

PKFY-P63VKM-E





CELSIUS AIR CONDITIONING LTD 1, WELL STREET HEYWOOD OL10 1NT Tel: 01706 367500

Fax: 01706 367355

Telephone: 01707 282880

Email: air.conditioning@meuk.mee.com Website: http://www.mitsubishielectric.co.uk/aircon

Mitsubishi Electric reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement.



