




## PUMY-P125VHMB

Y Series 5hp Outdoor Unit

R410A Heat Pump



- A two core non-polar transmission line allows for simple installation of up to 8 indoor units
- The condensing unit is extremely slimline which allows easy location and application of the system



Pictures not to scale




## **Product Details**


PUMY-P125VHMB	
Capacity (kW):	
Heating (Nominal)	16.0
Cooling (Nominal)	14.0
Heating (UK)	13.3
Cooling (UK)	12.9
Power Input (kW) Heating (Nominal)	4.33
Power Input (kW) Cooling (Nominal)	4.32
Power Input (kW) Heating (UK)	3.85
Power Input (kW) Cooling (UK)	3.66
Airflow(m3/min)	100
Noise (dBA)	50
Pipe Size Gas mm (in)	15.88 (5/8)
Pipe Size Liquid mm (in)	9.52 (3/8)
Width - mm	950
Depth - mm	330+30
Height - mm	1350
Weight - kg	127
Electrical Supply	220- 240v, 50Hz
Phase	Single
Mains Cable No. Cores	3
Starting Current (A)	5
Running Current (A) - Heating	18.3
Running Current (A) - Cooling	18.3
Fuse Rating (BS88) - HRC (A)	32

Piping Restrictions	
Total Piping Length (m)	120
Furthest Piping Length (m)	80
Furthest Piping Length after 1st Branch (m)	30
Between Indoor and Outdoor Units - Height (m)	50
Between Indoor and Indoor Units - Height (m)	12

## Dimension

## PUMY-P125VHMB







CELSIUS AIR CONDITIONING LTD 1, WELL STREET HEYWOOD OL10 1NT Tel: 01706 367500

Tel: 01706 367500 Fax: 01706 367355 Telephone: 01707 282880

Email: air.conditioning@meuk.mee.com Website: http://www.mitsubishielectric.co.uk/aircon

Mitsubishi Electric reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement.



