




PUHY-HP250YHM-A

Zubadan Y Series 10hp Outdoor Unit
R410A Heat Pump



- Stable Heating Performance Full heating capacity at -15 degrees C, which is a 40% capacity improvement over the standard YHM-A model
- Stable Operation -Utilising the new Flash Injection Circuit the Zubadan models have reduced defrost times and can provide continuous heating for up to 250mins
- Quick Start-Up Full heating capacity is achieved in about 20 mins, improving comfort levels
- Energy-saving 100% inverter driven outdoor compressor units with very low start currents.



Pictures not to scale


Product Details

PUHY-HP250YHM-A	
Capacity (kW):	
Heating (Nominal)	31.5
Cooling (Nominal)	28.0
Heating (UK)	33.39
Cooling (UK)	26.6
Power Input (kW) Heating (Nominal)	8.94
Power Input (kW) Cooling (Nominal)	9.06
Power Input (kW) Heating (UK)	14.3
Power Input (kW) Cooling (UK)	5.62
Max No. of Connectable Indoor Units	21
Airflow(m3/min)	225
Noise (dBA)	57
Width - mm	920
Depth - mm	760
Height - mm	1710
Weight - kg	220
Electrical Supply	380-415v, 50Hz
Phase	3
Mains Cable No. Cores	4 + earth
Starting Current (A)	8
Running Current (A) - Heating	13.8
Running Current (A) - Cooling	14
Fuse Rating (BS88) - HRC (A)	32


Piping Restrictions	
Total Piping Length (m)	300
Furthest Piping Length (m)	150
Furthest Piping Length after 1st Branch (m)	40
Between Indoor and Outdoor Units - Height (m)	50
Between Indoor and Indoor Units - Height (m)	15

Dimension


PUHY-HP250YHM-A



Front View)



Side View >



MITSUBISHI ELECTRIC

CELSIUS AIR CONDITIONING LTD 1, WELL STREET HEYWOOD OL10 1NT Tel: 01706 367500

Fax: 01706 367355

Telephone: 01707 282880 Email: air.conditioning@meuk.me

Email: air.conditioning@meuk.mee.com Website: http://www.mitsubishielectric.co.uk/aircon

Mitsubishi Electric reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement.



