

City Multi - Remote Controllers

The City Multi system is supported by a multitude of remote controllers. Each remote controller type, whilst being able to support the general control and monitoring functions for a group of indoor units, can also offer other unique operational features.



PAC-SE51CRA
Simplified remote controller



PAR-20MAA
Auto address remote controller



PAR-F27MEA
Energy save remote controller



PAR-FL31MA
Infra-red remote controller



PAC-SC30GRA
Group remote controller



PAC-SF41SCA
System remote controller



PAC-YT51CRA
Auto address remote controller

Technical Information >>

FUNCTION	DESCRIPTION	SIMPLIFIED REMOTE CONTROLLER PAC-SE51CRA		AUTO ADDRESS REMOTE CONTROLLER PAR-20MAA		ENERGY SAVE REMOTE CONTROLLER PAR-F27MEA		INFRA-RED REMOTE CONTROLLER PAR-FL31MA		GROUP REMOTE CONTROLLER PAC-SC30GRA		SYSTEM REMOTE CONTROLLER PAC-SF41SCA		AUTO ADDRESS REMOTE CONTROLLER PAC-YT51CRA	
		Operation	Display	Operation	Display	Operation	Display	Operation	Display	Operation	Display	Operation	Display	Operation	Display
ON/OFF	Run and Stop operation for a single group	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
MODE SELECTION	Switches between Cool/Dry/Auto/Fan/Heat. Operation Mode will vary depending on the indoor unit. Auto mode is available with only R2 and WVR2 systems		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓		✓
TEMPERATURE SETTING	Sets the groups temperature control. Cool/Dry: 19-30°C Heat: 17-28°C Auto: 19-28°C	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
FAN SPEED SETTING	4 speed - Lo-Mi1-Mi2-Hi 2 speed - Lo-Hi	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓			✓	✓
AIR FLOW DIRECTION	Air Flow angles: 100-80-60-40, and auto swing			✓	✓	✓	✓	✓	✓	✓	✓				
TIMER OPERATION	One ON/OFF time can be set. Interface with programme timer for additional options			✓	✓	✓	✓	✓	✓	✓	✓	✓	✓		
PERMIT/PROHIBIT FUNCTION	Run/Stop, Temperature Setting, Mode Selection and Filter Reset functions can be prohibited via a higher level system controller		✓		✓	✓	✓		✓		✓	✓	✓		✓
INDOOR RETURN AIR TEMPERATURE	Measures the intake temperature of the master unit within the group				✓		✓				✓				
ERROR INDICATION	Displays a 4 digit code and the affected unit address		✓		✓		✓		✓		✓		✓		✓
TEST RUN FUNCTION	Allows each unit within the group to operate in test mode		✓	✓	✓	✓	✓	✓	✓	✓	✓		✓		✓
VENTILATION INTERLOCK	Allows the group to be interlocked with a heat recovery Lossnay unit			✓	✓	✓	✓			✓	✓	✓	✓		
EXTERNAL INPUT/OUTPUT	Connection to the programme Timer PAC-SC32PTA, 7 day programme time with 2 time schedules, 48 start/stops per day			✓	✓	✓	✓			✓	✓	✓	✓		



This pdf has been downloaded from the website of :

“Supplying and installing the latest in air conditioning technology”

° Celsius
air conditioning

Celsius Air Conditioning Ltd, I Well Street, Heywood, Greater Manchester OL10 INT

 01706 367 500  07000 CELSIUS  01706 367 355  sales@celsiusair.co.uk  www.celsiusair.co.uk

www.celsiusair.co.uk